# **GEOMORPHIC CHANGE DETECTION U. SPATIAL COHERENCE & PROBABILISTIC BAYESIAN UPDATING**



April 30th to May  $1^{st}$ , 2014

Sponsored by:





Intermountain Center for River Rehabilitation and Restoration







### WORKSHOP PLAN – DAY 2... (AFTERNOON)



Q. Building your own FIS **Error Models** 





Self Paced – Change Detection

2:30 - 3:00

1:30 - 2:30

- 3:00 3:303:30 to 3:45 BREAK
- Τ. Interpreting Outputs
  - **U. Spatial Coherence & Bayesian**
- 4:15 to 4:45
- Recap / SLOP V.

3:45 to 4:15

4:45 to 6:00



## **PROBLEM WITH THRESHOLDING...** THE SMALL STUFF



## THIS IS FROM THE BACKGROUND READING

- Two methodological advances
  - 1. Fuzzy Inference Systems
  - 2. Spatial Coherence Filter & Bayesian Updating

EARTH SURFACE PROCESSES AND LANDFORMS Earth Surf. Process. Landforms 35, 136–156 (2010) Copyright © 2009 John Wiley & Sons, Ltd. Published online 10 December 2009 in Wiley InterScience (www.interscience.wiley.com) DOI: 10.1002(esp.1886

#### Accounting for uncertainty in DEMs from repeat topographic surveys: improved sediment budgets

#### Joseph M. Wheaton<sup>1</sup>, James Brasington<sup>2</sup>, Stephen E. Darby<sup>3</sup> and David A. Sear<sup>3</sup>

- <sup>1</sup> Department of Watershed Sciences, Utah State University, 5210 Old Main Hill, NR 210, Logan, UT 84322, USA
- <sup>2</sup> Institute of Geography & Earth Sciences, Aberystwyth University, Aberystwyth, SY23 3DB, UK
- <sup>3</sup> School of Geography, University of Southampton, Highfield, Southampton, SO17 1BJ, UK

Received 22 September 2008; Revised 26 June 2009; Accepted 6 July 2009

Correspondence to: Joseph M. Wheaton, Department of Watershed Sciences, Utah State University, 5210 Old Main Hill, NR 210, Logan, UT 84322, USA. E-mail: Joe.Wheaton@usu.edu



ABSTRACT: Repeat topographic surveys are increasingly becoming more affordable, and possible at higher spatial resolutions and over greater spatial extents. Digital elevation models (DEMs) built from such surveys can be used to produce DEM of Difference (DoD) maps and estimate the net change in storage terms for morphological sediment budgets. While these products are extremely useful for monitoring and geomorphic interpretation, data and model uncertainties render them prone to misinterpretation. Two new methods are presented, which allow for more robust and spatially variable estimation of DEM uncertainties and propagate these forward to evaluate the consequences for estimates of geomorphic change. The first relies on a fuzzy inference system to estimate the spatial variability of elevation uncertainty in individual DEMs while the second approach modifies this estimate on the basis of the spatial coherence of erosion and deposition units. Both techniques allow for probabilistic representation of uncertainty on a cell-by-cell basis and thresholding of the sediment budget at a user-specified confidence interval. The application of these new techniques is illustrated with 5 years of high resolution survey data from a 1 km long braided reach of the River Feshie in the Highlands of Scotland. The reach was found to be consistently degradational, with between 570 and 1970 m<sup>3</sup> of net erosion per annum, despite the fact that spatially, deposition covered more surface area than erosion. In the two wetter periods with extensive braid-plain inundation, the uncertainty analysis thresholded at a 95% confidence interval resulted in a larger percentage (57% for 2004-2005 and 59% for 2006-2007) of volumetric change being excluded from the budget than the drier years (24% for 2003-2004 and 31% for 2005-2006). For these data, the new uncertainty analysis is generally more conservative volumetrically than a standard spatially-uniform minimum level of detection analysis, but also produces more plausible and physically meaningful results. The tools are packaged in a wizard-driven Matlab software application available for download with this paper, and can be calibrated and extended for application to any topographic point cloud (x,y,z). Copyright © 2009 John Wiley & Sons 1td

KEYWORDS: DEM of Difference (DoD); fluvial geomorphology; morphological method; morphological sediment budgeting; River Feshie; fuzzy inference system

#### Introduction

With recent advances in ground-based, boat-based and remotely-sensed surveying technologies, the rapid acquisition of topographic data is now possible at spatial resolutions and extents previously unimaginable (Lane and Chandler, 2003; Heritage and Hetherington, 2007; Milan et al., 2007; Marcus and Fonstad, 2008; Notebaert et al., 2008). These advances make monitoring geomorphic changes and estimating sediment budgest through repeat topographic surveys and the applications of the morphological method (Church and Ashmore, 1998) a tractable, affordable approach for monitoring applications in both research and practice. In fluvial geomorphology, the morphological approach has been used as an alternative to measuring sediment transport directly and has historically been applied primarily to repeat surveys of river plan form, cross-sections and/or longitudinal profiles (Brewer and Passmore, 2002; Lane, 1998). However, from the early 19906; Lane et al., 1994), the morphological method has been expanded to include the use of repeat topographic surveys from which digital elevation models (DEMs) could be constructed and differenced to produce DEMs of Difference (DoDs). This paper focuses exclusively on the 2D application of the morphological method using DoDs.

Uncertainty in DoD application of the morphological method has already received considerable attention (Lane et al., 1994; Milne and Sear, 1997; Brasington et al., 2000; Lane, 1998; Lane et al., 2003). Driving this interest has been the basic question that, given the uncertainty inherent in individual DEMs, is it possible to distinguish real geomorphic changes from noise? Repeat surveys using rRCJPS (Brasington et al., 2000), total stations (Milne and Sear, 1997), aerial photogrammetry (Winterbottom and Gilvear, 1997; Westaway et al., 2001), multi-beam echo-sounding (Calder and Mayer,



### **DETAIL PLAN – I.**

#### I. Alternative Approaches to Geomorphic Change Detection

## A. Coherence Filter & Bayes Theorem



Run Spatial Coherence Filter & Do Bayesian Updating



# **SPATIAL COHERENCE OF CHANGE?**

- Is change map a checkerboard of blue and red or do changes exhibit coherent spatial patterns?
- PREMISE:
  - Change is more believable if it is spatially consistent with its neighbors



# **SPATIAL COHERENCE FILTER**

- Normally, if a cell is below minLoD it is discarded
- Let normal  $_{min}LoD = -5 \text{ cm}$
- If everything around me is also erosional, there is a higher likelihood that the small change is real
- By contrast, if everything around me is depositional, then lower probability that change is real





## **UPDATE USING BAYES THEOREM**

 $p(E_j|A) = \frac{p(A|E_J) p(E_j)}{p(A|E_J) p(E_j) + p(A|E_i) p(E_i)}$ 

P(E<sub>j</sub>|A) is updated (posterior probability)
P(E<sub>j</sub>) is initial probability (a priori

probability)
P(A|E<sub>j</sub>) is conditional probability using spatial coherence filter (new information)
Subscript *i* denotes inverse probability





## **EXAMPLE: WHAT IS** $P(E_j|A)$ ?



LET: •  $P(E_j) = 0.68$ •  $P(A|E_j) = 0.85$ • In other words, additional information from spatial coherence index increased probability that change is real....





## **INFLUENCE OF SPATIAL COHERENCE FILTER**

Effectively a better spatial discriminator
For ECD, recovers some low magnitude changes



R





Thresholded based on Spaital Coherence:2006-2005





UtahStateUniversity ECOGEOMORPHOLOGY & TOPOGRAPHIC

## **USEFULL BUT... BE CAREFUL**

- We get an updated map of probability that change is real
- Be careful with systematic errors...
- Could be used with other conditional probabilities...





### DETAIL PLAN – I.

#### I. Alternative Approaches to Geomorphic Change Detection

# A. Coherence Filter & Bayes Theorem

#### B. Run Spatial Coherence Filter & Do Bayesian Updating



## **RUNNING BAYESIAN UPDATING IN GCD**

